

DATASHEET

GLASS PHASE LOSS Island 11 MM

with steel reel incl. new double discharge system

Art.-No.: 10092 | 10093 | 10094 | 10095 | **10096** | 10097



VIDEO

Glasfaserstäbe
Ø 7.5 mm, 9 mm
and 11 mm

Click here
Video

STABSPITZE:
Shackles, stainless steel, with
RUNPOTEC thread RTG Ø12 mm,
screwed with **strand**

STABENDE:
End sleeve, stainless steel, with
RUNPOTEC thread
RTG Ø12 mm

Click here Product
information

automatic
with run-off brake

quick-release
bearing
Rollers

Mechanical counter

Adaptable Führungsonde

Data

ART.-NR.	10092	10093	10094	10095	10096	10097
LENGTH	100 m	120 m	150 m	200 m	250 m	300 m
WEIGHT KG	31,6	34,3	38,7	45,6	53,2	59,6
MATERIAL-STAB	Glass fibre core with PP sheathing					
Rohr Island	optimal from 80 - 250 mm					
Gesamtbruch-last	580 kg					

ADVANTAGES

- ✓ incl. steel reel and meter counter
- ✓ **Double discharge system**
(automatic outlet brake and quick run-out)
- ✓ **Additional parking brake**
- ✓ **Glass fibre rod total breaking load up to 6200 kg**
- ✓ **Total breaking load 580 kg**
- ✓ **Biegeradius 770 mm**

Recommended pipe diameter, bending radius and total breaking load of the glass fibre rod Ø 11 mm

Island				
11 mm	80 - 250 mm	770 mm	6200 kg	580 kg

DESCRIPTION

Cable retractor glass fibre rod Ø 11 mm - RUNPOTEC thread RTG Ø 12 mm with robust steel reel (galvanized/powder-coated) Ø 1000 mm incl. new double outlet system (automatic outlet remseand quick run-out), additional parking brake. The shackle also has a transition thread on RTG Ø 6 mm to adapt various guide rods (RUNPOSTICKS), guide probes, cable pulling stockings, multifunction camera RC 2 and the like. Glass fibre rod Total breaking load 6200 kg, total breaking load 580 kg.

Optimal area of application: for pipe diameters 80 - 250 mm

Application film: you can watch a short, very informative application film by scanning the QR code or viewing on www.runpotec.com

Scope of delivery: 1 piece glass fibre rod Ø 11 mm with steel reel and new double outlet system, end sleeves on both sides (start/end), 1 x meter counter, 1 x shackle

INFORMATION

Use with:

RUNPOCAM RC2

Lengths: 10 m | 30 m | 50 m

Art.-No.: 10139 | 10140 |

